Setback & Lot Requirements

ARTICLE IV, SECTION 405

SCHEDULE OF YARD AND LOT REQUIREMENTS **ZONING DISTRICTS AND DWELLINGS**

DISTRIC T	MIN. LOT AREA PER FAMILY	MIN. ROAD FRONTAG E	MIN FRONT YARD SETBAC K	MIN. REAR YARD SETBAC K	MIN. SIDE YARD SETBAC K	SUM OF SIDES SETBAC K	MIN. LIVIN G AREA PER UNIT SQ. FT.	WATER,SEPTIC & SEWER FACILITIES
А	5 Acres (1) (3)	300 ft.	70	40	40	80	1800	ON-SITE
Е	3 Acres (1) (3)	150 ft.	50	40	20	40	1800	ON-SITE
R-1	1/2 Acre PUD Recommende d		40	40	10	25	1800	OFF-SITE
R-M	2/1 Ratio PUD Recommende d	Unit to green space					900	ON-SITE

1. Corner lots shall require the same frontage per street.

 Maximum height of buildings shall be thirty five (35) feet and 2 1/2 stories high.
A minimum of 1,000 square feet living area shall be bounded by the foundation in all districts except R-M District

4. Minimum lot road frontage for a "cul-de-sac" lot width will be determined at the setback line.